

فن کویل دیواری / Wall Mounted Fancoil

■ ظرفیت هوادهی از ۲۰۰ تا ۶۰۰ فوت مکعب بر دقیقه

■ دارای ریموت کنترل با صفحه نمایشگر LED

■ دارای شیر سه راهه

■ دارای الکتروموتور ۴ سرعته



AMKG			300	400	600
Power supply		V/Ph/Hz	220-240/1/50		
Air flow (H/M/L)		m ³ /h	510/430/380	680/580/510	1020/870/770
		CFM	300/250/220	400/340/300	600/510/450
Cooling	Capacity (H/M/L)	kW	2.64/2.24/2.05	3.08/2.62/2.27	4.45/4.18/3.74
	Water flow rate	l/h	454	530	765
	Water pressure drop	kPa	18	22	29
Heating	Capacity (H/M/L)	kW	3.69/3.25/2.77	4.34/3.86/3.25	6.3/5.67/4.73
	Water pressure drop	kPa	16.4	20.8	27.9
Power input (H/M/L)		W	40/32/28	44/35/31	60/48/42
Sound pressure level (H/M/L)			35/29/24	37/31/26	40/34/29
Fan motor	Type	Low noise 3-speed fan motor			
	Quantity	1			
Fan	Type	Tangential fan			
	Quantity	1			
Coil	Row	2			
	Max. working pressure	MPa	1.6		
	Diameter	mm	Φ 7		
Net dimensions (W×H×D)		mm	915×290×210	915×290×210	1070×315×210
Packing size (W×H×D)		mm	1020×385×300	1020×385×300	1180×410×300
Net weight		kg	12	12	15
Gross weight		kg	16.7	17	19
Water inlet/outlet pipe		inch	G3/4		
Drain pipe		mm	ODΦ20		